



**Safety storage cabinet Q-CLASSIC-90**  
**Model Q90.195.090, body colour anthracite grey**  
**(RAL 7016), with wing doors in asecos silver**

**Safe and approved storage of flammable hazardous substances in working areas**

**Function / construction:**

- **Robust construction and longevity:** triple hinged door, safety elements assembled outside the storage compartment for increased protection against corrosion, scratch- and impact-resistant surface, easy to clean
- **No unauthorised use:** doors lockable with cylinder locking (integration in an existing locking system possible) and locking state indicator (red/green)
- **Easy transport:** integrated transport base with removable, optional base cover
- **Easy alignment:** adjusting aids to compensate for uneven floor
- **Ventilation:** integrated air ducts ready for connection (DN 75) to a technical exhaust system, spinning wheel in the exhaust grid as an indicator of sufficient technical ventilation

**Dimensions**

Width (external)	893 mm
Depth (external)	615 mm
Height (external)	1953 mm
Width (internal)	750 mm
Depth (internal)	522 mm
Height (internal)	1647 mm

The available internal dimensions can vary depending on the interior equipment package.

**Weight / Load**

Weight without interior equipment	343 kg
Distributed load	654 kg/m <sup>2</sup>
Maximum load	600 kg

**Ventilation**

Extraction air	75 DN
minimum exhaust air quantity 10 times	6 m <sup>3</sup> /h
Pressure drop inside the cabinet	5 Pa


**Colouring / Surface finish**

Body colour code	RAL 7016
Body colour	anthracite grey
Body surface finish	textured
Door / Drawer colour	asecos silver
Door / Drawer surface finish	textured


**General Information**

Number of doors	2
Door opening angle	89.50°
Depth with open doors	1015 mm
Interior grid dimension	32 mm
Entry width transport base	820 mm
Entry height transport base	90 mm
Customs tariff number	94032080

Front view



Side view



Top view

