

Model K90.196.120.MF.FWAS



| Dimensions | |
|---|------------|
| Width (external) | 1197.00 mm |
| Depth (internal) | 522.00 mm |
| Height (external) | 1969.00 mm |
| Width (internal) | 450.00 mm |
| Depth (external) | 617.00 mm |
| Height (internal) | 1742.00 mm |
| The available internal dimensions can vary depending on the interior equipment package. | |

| Weight / Load | |
|-----------------------------------|--------------|
| Weight without interior equipment | 515 kg |
| Distributed load | 576.00 kg/m² |
| Maximum load | 600 kg |
| | |
| Ventilation | |
| Extraction air | 75 DN |

9 m3/h

minimum exhaust air quantity 10 times

Pressure drop inside the cabinet

| Colouring / Surface finish | |
|------------------------------|------------|
| Body colour code | RAL 7035 |
| Body colour | Light grey |
| Body surface finish | plain |
| Door / Drawer colour code | RAL 7035 |
| Door / Drawer colour | Light grey |
| Door / Drawer surface finish | plain |

| General Information | |
|-----------------------|---|
| Left compartment | Compartment for the storage of flammable liquids |
| Right compartment | Compartment for the storage of aggressive, non flammable hazardous materials |
| Depth with open doors | 1178 mm |
| Customs tariff number | 94032080 |





Combi safety storage cabinet K-PHOENIX-90 Model K90.196.120.MF.FWAS, in light grey (RAL 7035)

Safe and approved storage of aggressive and flammable hazardous substances in working areas

Function / construction:

- Robust construction and longevity: triple hinged door, body made of powder-coated sheet steel, safety elements assembled outside the cabinet for increased protection against corrosion
- **two in one:** 2 compartments (vertical seperated) allow the storage of flammable liquids and aggressive chemicals in one cabinet
- user-friendly and safe (folding door compartment): door open arrest system (standard), convenient and safe removal or storage of containers
- **no unauthorised use:** doors lockable with profile cylinder (integration in an existing locking system possible) / cylinder lock
- easy alignment: adjusting aids to compensate for uneven floor
- **Ventilation:** integrated air ducts ready for connection (DN 75) to a technical exhaust system







