


Model K90.196.120.MF.FWAC



Dimensions	
Width (external)	1197.00 mm
Depth (internal)	524.00 mm
Height (external)	1969.00 mm
Width (internal)	450.00 mm
Depth (external)	617.00 mm
Height (internal)	1742.00 mm
The available internal dimensions can vary depending on the interior equipment package.	

Weight / Load	
Weight without interior equipment	515 kg
Distributed load	576.00 kg/m²
Maximum load	600 kg
Ventilation	
Extraction air	75 DN
Minimum exhaust air quantity 10 times	9 m³/h
Differential pressure (10 times air change)	5 Pa

Colouring / Surface finish	
Body colour code	
Body colour	Laboratory white (sim. RAL 9016)
Body surface finish	plain
Door / Drawer colour code	
Door / Drawer colour	Laboratory white (sim. RAL 9016)
Door / Drawer surface finish	plain

General Information	
Left compartment	Compartment for the stor- age of flammable liquids
Right compartment	Compartment for the storage of aggressive, non flammable hazardous materials
Depth with open doors	1178 mm
Customs tariff number	94032080





Combi safety storage cabinet K-PHOENIX Vol.2-90 Model K90.196.120.MF.FWAC, laboratory white (sim. RAL 9016)

Safe and approved storage of aggressive and flammable hazardous substances in working areas

Function / construction:

- Robust construction and longevity: triple hinged door, body made of powder-coated sheet steel, safety elements assembled outside the cabinet for increased protection against corrosion
- Two in one: 2 compartments (vertical seperated) allow the storage of flammable liquids and aggressive chemicals in one cabinet
- User-friendly and safe (folding door compartment): door open arrest system (standard), convenient and safe removal or storage of containers
- Always closed (folding door compartment): serial automatic door closing (TSA) releases the arrested door after approx. 60 seconds; acoustic and visual signal before closing
- No unauthorised use: doors lockable with profile cylinder (integration in an existing locking system possible) / cylinder lock
- Easy alignment: adjusting aids to compensate for uneven floor
- **Ventilation:** integrated air ducts ready for connection (DN 75) to a technical exhaust system

