

## Model SL.196.060.MH



| Dimensions   |            |
|--|------------|
| Width (external)   | 597.00 mm  |
| Depth (external)   | 603.00 mm  |
| Height (external)  | 1965.00 mm |
| Width (internal)   | 485.00 mm  |
| Depth (internal)   | 570.00 mm  |
| Height (internal)  | 914.00 mm  |
| The available internal dimensions can vary depending on the interior equipment package |            |

| Weight / Load                               |              |
|---|--------------|
| Weight without interior equipment           | 125 kg       |
| Distributed load                            | 444.00 kg/m² |
| Maximum load                                | 300 kg       |
|   |              |
| Ventilation                                 |              |
| Extraction air                              | 75 DN        |
| recom. exhaust air quantity 30 times        | 8 m³/h       |
| Differential pressure (30 times air change) | 40 Pa        |

40 Pa

1119 mm

minimum exhaust air quantity 10 times Pressure drop inside the cabinet

Number of doors

Depth with open doors

**Customs tariff number** 

| Colouring / Surface finish   |                                     |
|------------------------------|-------------------------------------|
| Body colour code             |                                     |
| Body colour                  | Laboratory white (sim. RAL<br>9016) |
| Body surface finish          | plain                               |
| Door / Drawer colour code    |                                     |
| Door / Drawer colour         | Laboratory white (sim. RAL<br>9016) |
| Door / Drawer surface finish | plain                               |
| General Information          |                                     |









Cabinet for acids and alkalis SL-CLASSIC Model SL.196.060.MH, laboratory white (sim. RAL 9016)

Safe and approved storage of aggressive, non flammable hazardous materials in working areas

## **Function / construction:**

- Robust construction and longevity: cabinet body made of powder-coated sheet steel, safety elements assembled outside the storage compartment for increased protection against corrosion
- **Two in one:** two hermetically separated storage compartments allow the isolated storage of acids and bases in one cabinet
- **No unauthorised use:** doors lockable with profile cylinder (integration in an existing locking system possible)
- Easy alignment: adjusting aids to compensate for uneven floor
- **ventilation:** integrated metal-free air ducts ready for connection to a technical exhaust system with only one extraction air inlet

Front view Side view





