

Model SL.196.060.MH.R





Weight / Load	
Weight without interior equipment	125 kg
Distributed load	444.00 kg/m²
Maximum load	300 kg
Ventilation	
Extraction air	75 DN
recom. exhaust air quantity 30 times	8 m³/h
Differential pressure (30 times air change)	40 Pa
minimum exhaust air quantity 10 times	5 m³/h
Pressure drop inside the cabinet	40 Pa
Colouring / Surface finish	

Body colour code	RAL 7035
Body colour	Light grey
Body surface finish	plain
Door / Drawer colour code	RAL 7035
Door / Drawer colour	Light grey
Door / Drawer surface finish	plain

General Information	
Number of doors	2
Depth with open doors	1119 mm
Customs tariff number	94032080










Cabinet for acids and alkalis SL-CLASSIC Model SL.196.060.MH.R, light grey (RAL 7035)


Safe and approved storage of aggressive, non flammable hazardous materials in working areas

Function / construction:

- Robust construction and longevity: cabinet body made of powder-coated sheet steel, safety elements assembled outside the storage compartment for increased protection against
- **Two in one:** two hermetically separated storage compartments allow the isolated storage of acids and bases in one cabinet
- No unauthorised use: doors lockable with profile cylinder (integration in an existing locking system possible)
- Easy alignment: adjusting aids to compensate for uneven floor
- ventilation: integrated metal-free air ducts ready for connection to a technical exhaust system with only one extraction air inlet

Front view Side view








Diagram shows left-hinged door. Dimensions are identical for a right-hinged fitting.