



**Gas cylinder cabinet G-OD**  
**Model GOD.215.100, light grey (RAL 7035)**

**Safe and approved outdoor storage of flammable or toxic gases – for up to 3 x 50-litre gas cylinders**

**Function / construction:**

- **Robust construction and longevity:** completely galvanised and powder-coated structured surface and stainless steel base
- **No unauthorised use:** lockable turning lever (doors also available with profile cylinder, compatible for locking system)
- **Easy alignment:** adjusting aids to compensate for uneven floor
- **Easy mounting of connecting pipes and gas fittings:** lead-through points in the ceiling of the cabinet
- **Ventilation:** effective ventilation through openings beneath the doors and at the rear wall

**Dimensions**

Width (external)	1006.00 mm
Depth (external)	400.00 mm
Height (external)	2149.00 mm
Width (internal)	995.00 mm
Depth (internal)	370.00 mm
Height (internal)	2070.00 mm

The available internal dimensions can vary depending on the interior equipment package.

**Weight / Load**

Weight without interior equipment	113 kg
Distributed load	509.00 kg/m <sup>2</sup>
Maximum load	600 kg

**Ventilation**

Extraction air	75 DN
Minimum exhaust air quantity 10 times	8 m <sup>3</sup> /h
Lead-through possibilities	12

**Colouring / Surface finish**

Body colour code	RAL 7035
Body colour	Light grey
Body surface finish	textured
Door / Drawer colour code	RAL 7035
Door / Drawer colour	Light grey
Door / Drawer surface finish	textured

**General Information**

Number of doors	2
Door opening angle	180.00°
Depth with open doors	895 mm
x 50-litre gas cylinders	3 piece
Customs tariff number	94032080

