


Function / construction:

- **Robust construction and longevity:** sturdy sheet-steel construction
- **No unauthorised use:** doors lockable with cylinder locking (integrated in the turning handle)
- **Type 30 safety box:** for proper storage of flammable hazardous materials in work rooms, according to EN 14470-1 (type 30) and TRGS 510, 2 self-closing hinged doors, bottom collecting sump, powder-coated steel with 8.5 litres volume and exhaust air connection (DN 75) for technical ventilation of the safety box

Dimensions

Width (external)	950.00 mm
Depth (external)	500.00 mm
Height (external)	1950.00 mm
Width (internal)	945.00 mm
Depth (internal)	460.00 mm
Height (internal)	1845.00 mm

The available internal dimensions can vary depending on the interior equipment package.

Weight / Load

Weight without interior equipment	150 kg
Distributed load	316.00 kg/m ²
Maximum load	300 kg

Ventilation

Extraction air	75 DN
minimum exhaust air quantity 10 times	8 m ³ /h
Pressure drop inside the cabinet	2 Pa

Colouring / Surface finish

Body colour code	RAL 7035
Body colour	Light grey
Door / Drawer colour code	RAL 1004
Door / Drawer colour	Warning yellow

General Information

Number of doors	2
Customs tariff number	94032080

For further information please visit www.asecos.com