asecos

ID-Nr. 32933-050 Model CX.229.105.MM.4WD



Dimensions	
Width (external)	1055.00 mm
Depth (external)	520.00 mm
Height (external)	2290.00 mm
Width (internal)	475.00 mm
Depth (internal)	495.00 mm
Height (internal)	905.00 mm

The available internal dimensions can vary depending on the interior equipment package.

Weight / Load	
Weight without interior equipment	98 kg
Distributed load	435.00 kg/m ²
Maximum load	600 kg
Electrical component	
Frequency	50 Hz
Nominal voltage	230 V
Maximum current consumption	0.5 A
Power consumption in operation	120 W
Power consumption in standby mode	50 W
Colouring / Surface finish	
Body colour code	RAL 7016
Body colour	anthracite grey
Body surface finish	textured
Door / Drawer colour code	RAL 9010
Door / Drawer colour	Pure white
Door / Drawer surface finish	textured
General Information	
Number of doors	2
Door opening angle	110.00%

Number of doors	2
Door opening angle	110.00°
Depth with open doors	1026 mm
Customs tariff number	94032080



Recirculating air filter storage cabinet CX-CLASSIC-MultiRisk

Model CX.229.105.MM.4WD, body colour anthracite grey (RAL 7016), with wing doors in pure white (RAL 9010)

Safe, approved and separated storage of waterpollutant, non-flammable liquids and toxics in working areas according to TRGS 510

Function / construction:


Cabinet body


- Robust construction and longevity: robust, high-quality, scratch-resistant outer body with powder-coated textured surface
- All in one: different compartments (multiple seperation) allow the storage of different hazardous materials in one cabinet
- **no unauthorised use:** doors lockable with cylinder locking (integrated in the turning handle)
- easy alignment: adjusting aids to compensate for uneven floor

Recirculating air filter system


- Ideal for the direct installation in working areas very low noise, only approx. 39 dB (A)
- With multi-stage wideband filter
- VDE approved monitoring electronics (extraction monitoring) incl. cool-device cable
- Optical and acoustical alarm including potential-free alarm contact
- Display with innovative touch panel
- Manual check of the filter saturation


Front view











CX.229.105.WDFW / CX.229.105.MM.4WD

CX.229.081.WDFW

