

Model FX30.229.086.WDFW



Dimensions	
Width (external)	864.00 mm
Depth (external)	620.00 mm
Height (external)	2294.00 mm
Width (internal)	750.00 mm
Depth (internal)	519.00 mm
Height (internal)	1626.00 mm
The available internal dimensions can vary depending on the interior equipment package.	

Weight / Load	
Weight without interior equipment	245 kg
Distributed load	608.00 kg/m ²
Maximum load	600 kg

Electrical component		
Frequency	50 Hz	
Nominal voltage	230 V	
Maximum current consumption	0.5 A	
Power consumption in operation	120 W	
Power consumption in standby mode	50 W	

Colouring / Surface finish	
Body colour	anthracite grey
Body surface finish	textured
Door / Drawer colour code	RAL 3020
Door / Drawer colour	Traffic red
Door / Drawer surface finish	textured

General Information	
Number of doors	1
Door opening angle	90.00°
Depth with open doors	1394 mm
Customs tariff number	94032080













Recirculating air filter storage cabinet FX-DISPLAY-30 Model FX30.229.086.WDFW, body colour anthracite grey, with glass-fronted wing door in traffic red (RAL 3020)

Safe and approved storage of flammable liquids and further hazardous substances

Function / construction:


Cabinet body


- Robust construction and longevity: triple hinged door, cabinet body made of melamine resin and flame retardant special plates, safety elements assembled outside the storage compartment for increased protection against corrosion, doors with metal front as well as scratch-and impact-resistant surface, easy to clean
- All containers at a glance: door with large glass cutout allows a quick and easy overview of the stored containers – even with closed doors
- Easy handling with comfort: door stops in any position, self-closing in the event of fire
- **No unauthorised use:** door lockable with profile cylinder (integration in an existing locking system possible)
- Easy transport: integrated transport base with removable, optional base cover or adjusting aids with base cover
- easy alignment: adjusting aids to compensate for uneven floor

Recirculating air filter system

- Ideal for the direct installation in working areas very low noise, only approx. 39 dB (A)
- With multi-stage wideband filter
- VDE approved monitoring electronics (extraction and filter monitoring) incl. cool-device cable
- Optical and acoustical alarm including potential-free alarm contact
- Display with innovative touch panel
- ATEX compliant: C € II 3/-G Ex ic nA IIB T4 Gc

Front view Side view





Top view

