

Model FX90.229.120.MV



Dimensions	
Width (external)	1193.00 mm
Depth (external)	615.00 mm
Height (external)	2294.00 mm
Width (internal)	450.00 mm
Depth (internal)	522.00 mm
Height (internal)	1647.00 mm
The available internal dimensions can vary depending on the	he interior equipment package.

Weight / Load	
Weight without interior equipment	554 kg
Distributed load	595.00 kg/m²
Maximum load	600 kg

Electrical component		
Frequency	50 Hz	
Nominal voltage	230 V	
Maximum current consumption	0.5 A	
Power consumption in operation	120 W	
Power consumption in standby mode	50 W	

Colouring / Surface finish	
Body colour code	RAL 7016
Body colour	anthracite grey
Body surface finish	textured
Door / Drawer colour code	RAL 1004
Door / Drawer colour	Warning yellow
Door / Drawer surface finish	textured

General Information	
Number of doors	2
Door opening angle	89.50°
Depth with open doors	1165 mm
Customs tariff number	94032080













Recirculating air filter storage cabinet FX-CLASSIC-90 Model FX90.229.120.MV, body colour anthracite grey (RAL 7016), with wing doors in warning yellow (RAL 1004)

Safe and approved storage of flammable liquids and further hazardous substances

Function / construction:

Cabinet body

- Robust construction and longevity: triple hinged door, safety elements assembled outside the storage compartment for increased protection against corrosion, scratch- and impact-resistant surface, easy to clean
- **two in one:** 2 compartments (vertical separation) allow the separated storage of different hazardous materials in one cabinet
- Easy handling with comfort: doors stop in any position, self-closing in the event of fire
- No unauthorised use: doors lockable with cylinder locking (integration in an existing locking system possible) and locking state indicator (red/green)
- easy transport: integrated transport base with removable, optional base cover
- easy alignment: adjusting aids to compensate for uneven floor

Recirculating air filter system

- Ideal for the direct installation in working areas very low noise, only approx. 39 dB (A)
- With multi-stage wideband filter
- VDE approved monitoring electronics (extraction and filter monitoring) incl. cool-device cable
- Optical and acoustical alarm including potential-free alarm contact
- Display with innovative touch panel
- ATEX compliant: C € II 3/-G Ex ic nA IIB T4 Gc

Front view Side view





