

Model UB90.080.059.060.TR















Safe and approved storage of flammable hazardous substances in working areas

Function / construction:

- Robust construction and longevity: body made of powdercoated sheet steel
- Easy handling with comfort: door stops in any position, self-closing in the event of fire
- **User-friendly:** access to all containers, 93° opening of the wing door, interior of the cabinet completely visible
- **No unauthorised use:** door lockable with cylinder lock and locking state indicator (red/green)
- Mobile: castors with plinth (optionally available), easy moving of the cabinet
- **Ventilation:** integrated air ducts ready for connection (DN 50) to a technical exhaust system



Dimensions	
Width (external)	593.00 mm
Depth (external)	600.00 mm
Height (external)	800.00 mm
Width (internal)	470.00 mm
Depth (internal)	482.00 mm
Height (internal)	702.00 mm
The available internal dimensions can vary depend	ling on the interior equipment package.


Weight / Load	
Weight without interior equipment	143 kg
Distributed load	467.00 kg/m ²
Maximum load	300 kg


Ventilation		
Extraction air	50 DN	
Minimum exhaust air quantity 10 times	2 m³/h	
Differential pressure (10 times air change)	1 Pa	


Colouring / Surface finish	
Body colour code	RAL 7035
Body colour	Light grey
Body surface finish	plain
Door / Drawer colour code	RAL 7035
Door / Drawer colour	Light grey
Door / Drawer surface finish	plain

General Information		
1		
93.00°		
1044 mm		
94032080		


Front view Side view







Top view






Diagram shows left-hinged door. Dimensions are identical for a right-hinged fitting.