

Model UB90.060.140.050.UL.S2T




















Safety storage under bench cabinet UB-ST-90 Model UB90.060.140.050.UL.S2T, light grey (RAL 7035)

Safe and approved storage of flammable hazardous substances in working areas

Function / construction:

- Robust construction and longevity: body made of powdercoated sheet steel
- User-friendly and safe: door and drawer remain open in any
 position, interior of the cabinet completely visible access to all
 containers, 93° opening of the wing door
- Safe: drawer fitted with earthing wire incl. clamp as standard, seal welded sump, drawers are self-closing in the event of fire
- **No unauthorised use:** door and drawer lockable with cylinder lock and locking state indicator (red/green)
- Mobile: castors with plinth (optionally available), easy moving of the cabinet
- **Ventilation:** integrated air ducts ready for connection (DN 50) to a technical exhaust system



| Dimensions | |
|---|------------|
| Width (external) | 1402.00 mm |
| Depth (external) | 502.00 mm |
| Height (external) | 600.00 mm |
| Width (internal) | 1279.00 mm |
| Depth (internal) | 382.00 mm |
| Height (internal) | 502.00 mm |
| The available internal dimensions can vary depending on the interior equipment package. | |

| Weight / Load | |
|---|--------------------------|
| Weight without interior equipment | 205 kg |
| Distributed load | 240.00 kg/m ² |
| Maximum load | 300 kg |
| | |
| Ventilation | |
| Extraction air | 50 DN |
| Minimum exhaust air quantity 10 times | 3 m³/h |
| Differential pressure (10 times air change) | 1 Pa |

| Colouring / Surface finish | |
|------------------------------|------------|
| Body colour code | RAL 7035 |
| Body colour | Light grey |
| Body surface finish | plain |
| Door / Drawer colour code | RAL 7035 |
| Door / Drawer colour | Light grey |
| Door / Drawer surface finish | plain |

| General Information | |
|----------------------------|--------------|
| Number of drawers | 1 |
| Capacity drawer | 10.00 litres |
| Number of doors | 2 |
| Door opening angle | 93.00° |
| Depth with open doors | 918 mm |
| Customs tariff number | 94032080 |