

# Laminarflow Typ Silent-Standard

## Options overview

	Indicator lights and operation		LED		Front design					Substructure			Accessories			Suspension device				No. of fans
	B1: Display system ON - filter saturation	B2: Reduction mode	L1: High-performance LED ON/OFF	L2: High-performance LED dimmable	F1: Front panel (standard)	F2: Roller shutter	F3: Swinging front doors	F4: Strip curtain	F5: Sliding door	U1: Tabletop	U2: Table height-adjustable	U3: Lockable swivel casters	Z1: Timer	Z2: SMS-Notification	Z3: Suspension device	A1: M8 eyelets	A2: Stainless steel round strand rope	A3: M8 threaded rod 1m	A4: M8 threaded rod 2m	D1: Double fan ( from width 1800 mm)
Module (AM)	x	x	x	x				x					x	x	x	x	x	x	x	x
Table model (TM)	x	x	x	x	x	x			x		x		x	x	x	x	x			x
Floor model (BM)	x	x	x	x	x	x	x	x		x		x	x	x	x	x	x			x

**OPTION Double fan (D1):** For all modules, there is the option of installing a second fan for even quieter operation. From a width of 1800 mm, this is absolutely necessary in order to achieve a sufficient air volume.

### Order assistance:

(We will of course be happy to advise you on the order configuration by telephone or video conference).

### Example order code:

Silent-Standard type, table-top model with system ON, reduction and filter saturation displays and high-power LED ON/OFF, front panel and height-adjustable table, with timer and PLC connection.  
Special dimensions width x depth x height [in mm]: 1350x650x12850. (Customized to your individual requirements).

VCF\_SS-TM\_B1-B2-L1-F1-U2-Z1-Z4\_1350x650x1285